


PENDING CLAIMS AS AMENDED

Please amend the claims as follows:


- 
1. (withdrawn) A method for communication in a communication system, the communication system having a first cell, the first cell having a first sector and a second sector, the method comprising:
transmitting signals at a first power level to the first sector during a first time slot; and
transmitting signals at a second power level to the second sector during the first time slot.
 2. (withdrawn) The method of claim 1, wherein the second power level is less than the first power level.
 3. (withdrawn) The method of claim 1, further comprising:
transmitting signals at the second power level to the first sector during a second time slot;
and
transmitting signals at the first power level to the second sector during the second time slot.
 4. (withdrawn) The method of claim 3, further comprising:
transmitting a reverse power control signal to the first sector at the first power level during the second time slot.
 5. (withdrawn) A method for communication in a communication system, the communication system having a first cell, the first cell having a first sector and a second sector, the method comprising:
determining a time-division power assignment for the first sector and the second sector;
and
generating signals to the first sector and the second sector according to the power assignment.

6. (withdrawn) The method of claim 5, wherein the cellular communication system is a Code Division Multiple Access (CDMA) system.
7. (withdrawn) The method of claim 6, further comprising:
adjusting reverse power control signals according to the power assignment.
8. (withdrawn) The method of claim 6, further comprising:
adjusting a pilot signal according to the power assignment.
9. (Currently Amended) A mobile unit, comprising:
an antenna; and
an equalizer coupled to the antenna, the equalizer comprising:
a plurality of taps, each having first and second associated coefficients, the first associated coefficient corresponding to a first time slot, the second associated coefficient corresponding to a second time slot, the plurality of taps being operative to scale a first set of input symbols during the first time slot by the first associated coefficients, the plurality of taps being further operative to scale a second set of input symbols during the second time slot by the second associated coefficients, the plurality of taps being further operative to generate tap outputs and being equal to a total number of symbols per sample set;
a summing node coupled to the plurality of taps, the summing node being operative to sum the tap outputs; and
a memory storage unit adapted to store coefficient adjustment information, wherein the associated coefficients are adjusted according to the coefficient adjustment information.
10. (original) The mobile unit of claim 9, wherein the summing node is further operative to generate a C/I estimate for each time slot.

11. (original) The mobile unit of claim 10, further comprising:
a decision node operative to generate a data rate decision for each
time slot based on the C/I estimate.
12. (original) The mobile unit of claim 11, wherein the decision node comprises a look-up
table correlating C/I estimates and data rates.
13. (Currently Amended) An equalizer, comprising:
a plurality of taps being equal to a total number of symbols per sample set, the taps being
operative to scale input symbols with a first set of associated coefficients during a
first time slot and with a second set of associated coefficients during a second
time slot; and
a coefficient adjustment node coupled to the plurality of taps, the coefficient adjustment
node being operative to apply the first set of associated coefficients during the
first time slot and to apply the second set of associated coefficients during the
second time slot.
14. (original) The equalizer of claim 13, wherein the equalizer is an adaptive equalizer.
15. (original) The equalizer of claim 14, wherein the equalizer is operative to generate a C/I
estimate, the equalizer having $(2L+1)$ coefficients "C," the C/I estimate for a time slot "i" being
given as:

$$y_i(n) = \sum_{\ell=-L}^L C_{i,\ell}(n) \cdot x_i(n - \ell T),$$

wherein "n" is a sample set index, each sample set comprising a plurality of input symbols,
wherein "x" is an input symbol within a sample set, and wherein "T" is the period of the input
symbol, x.

- 
16. (original) The equalizer of claim 15, further comprising:
a data rate decision node operative to receive the C/I estimate and determine a
corresponding data rate.
17. (original) A mobile unit, comprising:
an equalizer adapted to calculate a first C/I estimate for a first transmitted signal power
and a second C/I estimate for a second transmitted signal power; and
a data rate decision node operative to receive C/I estimates from the equalizer and
generate a first data rate decision for the first C/I estimate and a second data rate
decision for the second C/I estimate.
18. (original) The mobile unit as in claim 17, wherein the first transmitted signal power is
received during a first time slot, and the second transmitted signal power during a second time
slot.
-